

Gusci a rullini
BAM1610-IKO - BAM1610-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1610-iko>



SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number				Shaft dia. mm (inch)	Housing bore dia. mm (inch)	Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g						
25.400 (1)	—	—	—	—	BAM 1610	25	—	—	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring
F _w	D	C	Shaft dia. mm (inch)	Housing bore dia. mm (inch)	Housing bore dia. mm (inch)				
25.400	31.750	15.881	25.400	25.387	31.764	11 300	18 100	15 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173238
Diametro interno	25.4 mm
Diametro esterno	31.75 mm
Spessore	15.88 mm
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE