


Gusci a rullini BAM1614-IKO - BAM1614-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1614-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
25.400 (1)	—	—	—	—	—	—	—	BAM 1614	33.5	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring
F_w	D	C	Shaft dia. mm	Housing bore dia. mm	J_7	C	C_0	rpm		
25.400	31.750	22.22	25.400	25.387	31.764	31.739	16 900	30 400	15 000	IRB 1214

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173252
Diametro interno	25.4 mm
Diametro interno	1" inch
Diametro esterno	31.75 mm
Diametro esterno	1 1/4" inch
Spessore	22.22 mm
Spessore	0.875" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE