

Gusci a rullini
BAM1710-IKO - BAM1710-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1710-iko>



SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series



Shaft dia. mm (inch)	Identification number							
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g
26.988 (1 1/8)	—	—	—	—	BAM 1710	26.5	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. d Max. Min.	Housing bore dia. H_7 Max. Min.	C	C_0	C_0	C_0	rpm	
26.988 (1 1/8)	33.338 (1 1/4)	15.88 (5/8)	26.988 Max. 26.975 Min.	33.352 Max. 33.327 Min.	11 600	19 200	14 000	—		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173313
Diametro interno	26.99 mm
Diametro esterno	33.34 mm
Spessore	15.88 mm
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE