


Gusci a rullini BAM186-IKO - BAM186-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam186-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g																													
	Standard	Mass (Ref.) g	Closed end																																							
28.575 (1 1/8)	—	—	—	—	—	—	—	—	—	—	—	—	—																													
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions mm(inch)</th> <th colspan="4">Standard mounting dimensions mm</th> <th rowspan="2">Basic dynamic load rating C</th> <th rowspan="2">Basic static load rating C₀</th> <th rowspan="2">Allowable rotational speed^(*) rpm</th> <th rowspan="2">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>Shaft dia. h_s</th> <th>Housing bore dia. J7</th> <th>Max.</th> <th>Min.</th> </tr> </thead> <tbody> <tr> <td>28.575 (1 1/8)</td> <td>34.925 (1 3/8)</td> <td>9.52 (3/8)</td> <td>28.575</td> <td>28.562</td> <td>34.939</td> <td>34.914</td> <td>6 330</td> <td>8 910</td> <td>13 000</td> <td>—</td> </tr> </tbody> </table>														Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring	F _w	D	C	Shaft dia. h _s	Housing bore dia. J7	Max.	Min.	28.575 (1 1/8)	34.925 (1 3/8)	9.52 (3/8)	28.575	28.562	34.939	34.914	6 330	8 910	13 000	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring																																
F _w	D	C	Shaft dia. h _s	Housing bore dia. J7	Max.	Min.																																				
28.575 (1 1/8)	34.925 (1 3/8)	9.52 (3/8)	28.575	28.562	34.939	34.914	6 330	8 910	13 000	—																																

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173368
Diametro interno	28.58 mm
Diametro esterno	34.93 mm
Spessore	9.52 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE