


Gusci a rullini BAM68-IKO - BAM68-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam68-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
9.525 ($\frac{3}{8}$)	—	—	—	—	—	—	—	BAM 68	6.1	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. h_8	Housing bore dia. J_7	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾	Assembled inner ring		
mm	mm	mm	Max.	Min.	Max.	Min.	N	N	rpm	
9.525	14.288	12.70	9.525	9.516	14.298	14.280	4 190	4 560	40 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173504
Diametro interno	9.53 mm
Diametro esterno	14.29 mm
Spessore	12.7 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE