

Gusci a rullini
BAM710-IKO - BAM710-IKO

<https://www.123cuscineti.it/cuscineti-supporti/cuscineti-rullini/gusci-rullini/bam710-iko>



SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

BAM BHAM

Shaft dia.		Identification number							
mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Mass (Grease retained) g
11.112 (3/8)	—	—	—	—	—	—	BAM 710	8.5	—

Boundary dimensions mm (inch)			Standard mounting dimensions mm				Basic dynamic load rating N	Basic static load rating N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
F _w	D	C	b ₂ Max.	Shaft dia. h8 Min.	Housing bore dia. J7 Min.	C					
11.112 (3/8)	15.875 (3/8)	15.88 (5/8)	1	11.112	11.101	15.885	15.867	6 020	7 550	35 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173528
Diametro interno	11.11 mm
Diametro esterno	15.88 mm
Spessore	15.88 mm
Imballaggio	1

contatto@123cuscineti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE