


## Cuscinetti conico

### 41106-41286-TIMKEN - 41106-41286-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/41106-41286-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |        |         | Load Ratings                            |                           |  |                           |  |       |       | Part Number |       |
|--------------------|--------|---------|---|---------------------------|--|---------------------------|--|-------|-------|-------------|-------|
| Bore d             | O.D. D | Width T | Dynamic <sup>10</sup><br>C <sub>1</sub> | Factor <sup>11</sup><br>e | Static <sup>12</sup><br>C <sub>0</sub> | Factor <sup>13</sup><br>K | Static <sup>14</sup><br>C <sub>2</sub> | Inner | Outer |             |       |
| mm                 | mm     | mm      | N                                       |                           | N                                      |                           | N                                      |       |       |             |       |
| 26.987             | 72.625 | 24.608  | 82000                                   | 3.07                      | 1.50                                   | 21400                     | 22500                                  | 0.57  | 84900 | 41106       | 41286 |
| 1.0625             | 2.850  | 0.9688  | 18000                                   |                           |  | 4820                      | 4960                                   |       | 14000 |             |       |

| Bearing Dimensions |        |               |  |  |  |  |                              |                              |                | Geometry Factors |                |     | Bearing Weight |      |
|--------------------|--------|---------------|--|--|--|--|------------------------------|------------------------------|----------------|------------------|----------------|-----|----------------|------|
| Width              |        | ER. Dr.<br>μm | Shaft  |  | Housing  |  | Cage                         |                              | G <sub>1</sub> | G <sub>2</sub>   | C <sub>3</sub> |     |                |      |
| B                  | C      |               | Max Shaft<br>Fillet Radius<br>R <sub>1</sub> | Backing<br>Shoulder Dia.<br>d <sub>1</sub> | Max Housing<br>Fillet Radius<br>r <sub>1</sub> | Backing<br>Shoulder Dia.<br>D <sub>1</sub> | A <sub>1</sub> <sup>10</sup> | A <sub>2</sub> <sup>11</sup> |                |                  |                |     |                |      |
| mm                 | mm     | mm            | mm   | mm   | mm   | mm   | mm                           | mm                           | mm             | mm               | mm             | mm  | kg             |      |
| 24.257             | 17.402 | -4.1          | 2.3  | 36.5                                       | 42.8   | 1.5  | 68.0                         | 61.8                         | 3.9            | 2.3              | 13.0           | 5.8 | 0.9088         | 0.49 |
| 0.9550             | 0.6875 | -0.16         | 0.09   | 1.44                                       | 1.65   | 0.06                                       | 2.69                         | 2.40                         | 0.12           | 0.09             |                |     |                | 1.07 |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952306841 |
| Diametro interno | 26.99 mm      |
| Diametro esterno | 72.63 mm      |
| Spessore         | 24.61 mm      |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE