


Cuscinetti conico 2560X-2523-TIMKEN - 2560X-2523-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/2560x-2523-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | | Part Number | |
|--------------------|--------|---------|--------------------------------------|------------------------|---------------------------------------|------------------------|-----------------------|-------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ¹⁾ C ₁ | Factor ²⁾ e | Dynamic ³⁾ C _{2e} | Factor ⁴⁾ K | Static C ₂ | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 30.080 | 69.850 | 23.812 | 82700 | 3.27 | 27000 | 10200 | 2.14 | 94000 | 2560X | 2523 | |
| 1.1811 | 2.7500 | 0.9375 | 18500 | | 4800 | 2200 | | 23200 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|-------------------------|--|--|--|--|------------------------------|------------------------------|------|------------------|----------------|----------------|----------------|------|
| Width B | Width C | ER. Dr. e ¹⁾ | Max Shaft Fillet Radius R ₁ ²⁾ | Backing Shoulder Dia. d _s ³⁾ | Max Housing Fillet Radius r ₁ ⁴⁾ | Backing Shoulder Dia. D _s ⁵⁾ | A ₁ ⁶⁾ | A ₂ ⁷⁾ | Cage | G ₁ | G ₂ | C ₃ | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg | |
| 25.267 | 19.850 | -0.4 | 2.8 | 36.8 | 38.5 | 1.3 | 64.0 | 61.0 | 8.8 | 8.8 | 25.6 | 9.6 | 0.9056 | 0.47 |
| 0.9953 | 0.7800 | -0.34 | 0.08 | 1.42 | 1.56 | 0.05 | 2.52 | 2.40 | 0.35 | 0.34 | | | 1.03 | |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | TIMKEN |
| N° Ean13 | 3663952309194 |
| Diametro interno | 30 mm |
| Diametro esterno | 69.85 mm |
| Spessore | 23.81 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE