


## Cuscinetti conico 2561X-2520-TIMKEN - 2561X-2520-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/2561x-2520-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Factor <sup>2)</sup> e	Dynamic <sup>3)</sup> C <sub>2</sub>	Factor <sup>4)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
30.213	66.421	25.400	82700	0.27	21700	16200	2.14	94600	2561X	2520
1.1895	2.6150	1.0000	18500		4800	2200		21200		

Bearing Dimensions										Geometry Factors			Bearing Weight							
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>						
Width B	Width C	ER. Dr. α <sup>1)</sup>	Max Shaft Fillet Radius R <sup>2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>3)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>4)</sup>	A <sub>2</sub> <sup>5)</sup>	A <sub>3</sub> <sup>6)</sup>				A <sub>4</sub> <sup>7)</sup>		A <sub>5</sub> <sup>8)</sup>	A <sub>6</sub> <sup>9)</sup>	A <sub>7</sub> <sup>10)</sup>	A <sub>8</sub> <sup>11)</sup>	A <sub>9</sub> <sup>12)</sup>	A <sub>10</sub> <sup>13)</sup>
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
24.714	28.626	-0.4	2.3	36.5	49.0	3.3	62.5	56.0	0.8	1.5	22.0	9.0	0.0050	0.41	0.91					
0.9730	0.8125	-0.34	0.09	1.44	1.97	0.13	2.46	2.24	0.03	0.06										

### CARATTERISTICHE DEL PRODOTTO

Marchio	TIMKEN
N° Ean13	3663952309897
Diametro interno	30.21 mm
Diametro esterno	66.42 mm
Spessore	25.4 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE