


Cuscinetti conico 4368-4335-TIMKEN - 4368-4335-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/4368-4335-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|--------|---------|--------------------------------------|------------------------|--------------------------------------|------------------------|-----------------------|--------|-------------|------|
| Bore d | O.D. D | Width B | Dynamic ¹⁾ C ₁ | Factor ²⁾ e | Dynamic ³⁾ C ₂ | Factor ⁴⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 34.925 | 90.488 | 39.688 | 109000 | 0.21 | 51900 | 25300 | 2100 | 294000 | 4300 | 4325 |
| 1.3750 | 3.5625 | 1.5625 | 44700 | | 11600 | 5040 | | 45800 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|-------------------------|--|--|---|--|-----------------------------------|------------------------------|------------------------------|------------------|----------------|----------------|----------------|------|
| Width B | Width C | ER. Dr. α ¹⁾ | Max Shaft Fillet Radius R ₁ ²⁾ | Backing Shoulder Dia. d ₁ ³⁾ | Max Housing Fillet Radius r ⁴⁾ | Backing Shoulder Dia. D ₁ ⁵⁾ | Cage A ₁ ⁶⁾ | A ₂ ⁷⁾ | A ₃ ⁸⁾ | G ₁ | G ₂ | C ₃ | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | kg | |
| 40.386 | 33.338 | -15.8 | 3.5 | 48.8 | 55.8 | 3.3 | 85.8 | 77.8 | 2.2 | 8.6 | 52.9 | 14.3 | 0.9872 | 5.36 |
| 1.5900 | 1.3125 | -0.59 | 0.14 | 1.93 | 2.17 | 0.13 | 3.35 | 3.03 | 0.09 | 0.33 | | | 0.281 | |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | TIMKEN |
| N° Ean13 | 3663952310275 |
| Diametro interno | 34.93 mm |
| Diametro esterno | 90.49 mm |
| Spessore | 39.69 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE